



LOGO! AM2 AQ EXPAN. MODULE, PU: DC 24V, 0/4-20MA 2AQ, 0-10V FOR LOGO! 8

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> • 12 V DC • 24 V DC 	<p>No</p> <p>Yes</p>
Analog outputs	
Number of analog outputs	2
Output ranges, voltage	
<ul style="list-style-type: none"> • 0 to 10 V 	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class B, for use in residential areas 	Yes
Degree and class of protection	
Degree of protection to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes
Standards, approvals, certificates	
CSA approval	Yes
UL approval	Yes
FM approval	Yes
Developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	

- Marine approval

Yes

Ambient conditions

Ambient temperature in operation

- Min.

0 °C

- max.

55 °C

Dimensions

Width

35.5 mm

Height

90 mm

Depth

58 mm

last modified:

23.04.2015