



SIMATIC S7, digital output SM 326, F-DO10x 24 V DC/2A PP, fail-safe digital output for SIMATIC S7F systems, with diagnostic alarm, LVV, up to Category 4 (EN 954-1)/ SIL3 (IEC61508)/PLE (ISO13849), 1x 40-pole

Supply voltage	
Rated value (DC)	24 V; 1L+
Reverse polarity protection	Yes
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V; 2L+, 3L+ No
Input current	
from supply voltage 1L+, max.	100 mA
from load voltage 2L+ (without load), max.	100 mA
from load voltage 3L+ (without load), max.	100 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	6 W
Digital outputs	
Number of digital outputs	10
Short-circuit protection	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	5 W
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	L+ (-1.0 V)
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> <li>for signal "1" permissible range for 0 to 40 °C, min.</li> <li>for signal "1" permissible range for 0 to 40 °C, max.</li> <li>for signal "1" permissible range for 40 to 60 °C, min.</li> <li>for signal "1" permissible range for 40 to 60 °C, max.</li> <li>for signal "0" residual current, max.</li> </ul>	2 A 7 mA 2.4 A 7 mA 2.4 A 0.5 mA
Switching frequency	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> <li>with inductive load, max.</li> <li>on lamp load, max.</li> </ul>	25 Hz 25 Hz 10 Hz
Total current of the outputs (per group)	
horizontal installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> <li>— up to 60 °C, max.</li> </ul>	10 A 6 A
vertical installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	5 A

<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
<b>Diagnostics indication LED</b>	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
<b>Potential separation</b>	
<b>Potential separation digital outputs</b>	
• between the channels	Yes
• between the channels, in groups of	5
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
<b>Isolation</b>	
Isolation tested with	370V for 1 min
<b>Standards, approvals, certificates</b>	
<b>Highest safety class achievable in safety mode</b>	
• acc. to DIN VDE 0801	AK 5 and 6
• acc. to EN 954	Cat. 4
• Performance level according to ISO 13849-1	e
• SIL acc. to IEC 61508	SIL 3
<b>Connection method</b>	
required front connector	40-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	330 g
<b>last modified:</b>	1/16/2021 