



Figure similar

SIMATIC S7-300, Analog input SM 331, Isolated 8 AI, resolution 13 bits
U/I/resistor/Pt100, NI100, NI1000, LG-NI1000, PTC/KTY, 66 ms conversion
time; 1x 40-pole

Input current	
from backplane bus 5 V DC, max.	90 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	8
• For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	30 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 kΩ
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	100 kΩ
• 1 V to 10 V	No
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	100 kΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
• -2.5 V to +2.5 V	No
• -250 mV to +250 mV	No
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
• -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	100 kΩ
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	100 kΩ
• -80 mV to +80 mV	No
Input ranges (rated values), currents	

<ul style="list-style-type: none"> ● 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) ● -10 mA to +10 mA ● -20 mA to +20 mA <ul style="list-style-type: none"> — Input resistance (-20 mA to +20 mA) ● -3.2 mA to +3.2 mA ● 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) 	Yes 100 Ω No Yes 100 Ω No Yes 100 Ω
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> ● Type B ● Type C ● Type E ● Type J ● Type K ● Type L ● Type N ● Type R ● Type S ● Type T ● Type U ● Type TXK/TXK(L) to GOST 	No No No No No No No No No No No No
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> ● Cu 10 ● Ni 100 <ul style="list-style-type: none"> — Input resistance (Ni 100) ● Ni 1000 <ul style="list-style-type: none"> — Input resistance (Ni 1000) ● LG-Ni 1000 <ul style="list-style-type: none"> — Input resistance (LG-Ni 1000) ● Ni 120 ● Ni 200 ● Ni 500 ● Pt 100 <ul style="list-style-type: none"> — Input resistance (Pt 100) ● Pt 1000 ● Pt 200 ● Pt 500 	No Yes; Standard/climate 100 MΩ Yes 100 MΩ Yes; Standard/climate 100 MΩ No No No Yes; Standard/climate 100 MΩ No No No
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> ● 0 to 150 ohms ● 0 to 300 ohms ● 0 to 600 ohms <ul style="list-style-type: none"> — Input resistance (0 to 600 ohms) ● 0 to 6000 ohms <ul style="list-style-type: none"> — Input resistance (0 to 6000 ohms) 	No No Yes 100 MΩ Yes 100 MΩ
Thermocouple (TC)	
Temperature compensation	
<ul style="list-style-type: none"> — parameterizable — internal temperature compensation — external temperature compensation with compensations socket 	No No No
Characteristic linearization	
<ul style="list-style-type: none"> ● parameterizable <ul style="list-style-type: none"> — for thermocouples — for resistance thermometer 	Yes No yes; Pt100 standard/air con.; Ni100 standard/air con.; Ni1000 standard/air con.; LG-Ni1000 standard/air con.
Cable length	
<ul style="list-style-type: none"> ● shielded, max. 	200 m; max. 50 m at 50 mV
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	

<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Basic conversion time (ms) Interference voltage suppression for interference frequency f1 in Hz 	13 bit Yes; 60 / 50 ms 66 / 55 ms 50 / 60 Hz
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> for voltage measurement for current measurement as 2-wire transducer for current measurement as 4-wire transducer for resistance measurement with two-wire connection for resistance measurement with three-wire connection for resistance measurement with four-wire connection 	Yes Yes; with external supply Yes Yes Yes Yes
Errors/accuracies	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> Voltage, relative to input range, (+/-) Current, relative to input range, (+/-) Resistance, relative to input range, (+/-) Resistance thermometer, relative to input range, (+/-) 	0.6 %; ± 0.6 % (± 5 V, 10 V, 1 to 5 V, 0 to 10 V); ± 0.5 % (± 50 mV, 500 mV, 1 V) 0.5 %; ± 20 mA, 0 to 20 mA, 4 to 20 mA 0.5 %; 0 to 6 kohms, 0 to 600 kohms 1 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic); 1.2 Kelvin (Pt100, Ni100, standard)
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> Voltage, relative to input range, (+/-) Current, relative to input range, (+/-) Resistance, relative to input range, (+/-) Resistance thermometer, relative to input range, (+/-) 	0.4 %; 0.4% (± 5 V, 10 V, 1 to 5 V, 0 to 10 V); 0.3% (± 50 mV, 500 mV, 1 V) 0.3 %; ± 20 mA, 0 to 20 mA, 4 to 20 mA 0.3 %; 0 to 6 kohms, 0 to 600 kohms 1 Kelvin (Pt100, Ni100, standard); 0.8 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic)
Interrupts/diagnostics/status information	
Diagnostics function	No
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm Limit value alarm 	No No
Diagnoses	
<ul style="list-style-type: none"> Diagnostic information readable 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> Group error SF (red) 	No
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> between the channels between the channels and backplane bus 	No Yes
Isolation	
Isolation tested with	500 V DC
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	250 g
last modified:	3/2/2021 