



Figure similar

SIMATIC S7-300, Analog input SM 331, single channel Isolated 250 V AC, 6 AI thermocouples Type B, E, J, K, L, N, R, S, T Voltage: +/-25mV to +/-1V 16 bit, 50ms, 1x 40-pole

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	150 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	2.2 W
Analog inputs	
Number of analog inputs	6
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
Constant measurement current for resistance-type transmitter, typ.	0.7 mA
Input ranges	
<ul style="list-style-type: none"> <li>Voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Current</li> </ul>	No
<ul style="list-style-type: none"> <li>Thermocouple</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Resistance thermometer</li> </ul>	No
<ul style="list-style-type: none"> <li>Resistance</li> </ul>	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>0 to +10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>1 V to 10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>-1 V to +1 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-10 V to +10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>-2.5 V to +2.5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>-250 mV to +250 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-250 mV to +250 mV)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-5 V to +5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>-50 mV to +50 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-500 mV to +500 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-500 mV to +500 mV)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>-80 mV to +80 mV</li> </ul>	Yes

— Input resistance (-80 mV to +80 mV)	10 MΩ
<b>Input ranges (rated values), currents</b>	
• 0 to 20 mA	No
• -10 mA to +10 mA	No
• -20 mA to +20 mA	No
• -3.2 mA to +3.2 mA	No
• 4 mA to 20 mA	No
<b>Input ranges (rated values), thermocouples</b>	
• Type B	Yes
— Input resistance (Type B)	10 MΩ
• Type C	Yes
— Input resistance (Type C)	10 MΩ
• Type E	Yes
— Input resistance (Type E)	10 MΩ
• Type J	Yes
— Input resistance (type J)	10 MΩ
• Type K	Yes
— Input resistance (Type K)	10 MΩ
• Type L	Yes
— Input resistance (Type L)	10 MΩ
• Type N	Yes
— Input resistance (Type N)	10 MΩ
• Type R	Yes
— Input resistance (Type R)	10 MΩ
• Type S	Yes
— Input resistance (Type S)	10 MΩ
• Type T	Yes
— Input resistance (Type T)	10 MΩ
• Type U	Yes
— Input resistance (Type U)	10 MΩ
• Type TXK/TXK(L) to GOST	Yes
— Input resistance (Type TXK/TXK(L) to GOST)	10 MΩ
<b>Input ranges (rated values), resistance thermometer</b>	
• Cu 10	No
• Ni 100	No
• Ni 1000	No
• LG-Ni 1000	No
• Ni 120	No
• Ni 200	No
• Ni 500	No
• Pt 100	No
• Pt 1000	No
• Pt 200	No
• Pt 500	No
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	No
• 0 to 300 ohms	No
• 0 to 600 ohms	No
• 0 to 6000 ohms	No
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes
— for definable comparison point temperature	Yes
<b>Characteristic linearization</b>	
• parameterizable	Yes

— for thermocouples	Type B, E, J, K, L, N, R, S, T, U, C, TXK, XK(L)
— for resistance thermometer	No
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation for the inputs</b>	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; Two's complement
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	30 / 50 / 60 / 300 ms
• Integration time (ms)	10/ 16.67/ 20/ 100 ms
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 / 400 Hz
<b>Encoder</b>	
Connection of signal encoders	
• for voltage measurement	Yes
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	Operating error at 0 ... 60 °C: $\pm 0.12\%$ @ $\pm 25$ mV, $\pm 0.08\%$ @ $\pm 50$ mV, $\pm 0.6\%$ @ $\pm 80$ mV, $\pm 0.05\%$ @ $\pm 250$ mV, $\pm 0.05\%$ @ $500$ mV, $\pm 0.05\%$ @ $\pm 1$ V
• Thermocouple, relative to input range, (+/-)	See manual for details
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	See manual for details
• Thermocouple, relative to input range, (+/-)	See manual for details
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; channel by channel
• Limit value alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
<b>Potential separation</b>	
Potential separation analog inputs	
• between the channels	Yes
• between the channels, in groups of	1
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
<b>Isolation</b>	
Isolation tested with	2 500 V DC
<b>Connection method</b>	
required front connector	40-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	272 g
<b>last modified:</b>	3/2/2021 